

DISTRIBUTOR/AGENT:	DATE OF ORDER:
	DATE OF DELIVERY:
	NAME OF THE ADDRESSEE/USER:



Product marked **CE**

FEATURES

- **Ergonomic and modular tricycle** that helps the user to keep a proper posture and makes the ride easier thanks to its design and components.
- **Lowered frame** for easy ascent and descent.
- **Front positioned bottom bracket** for easier pedaling.
- **Optimized pinion** to facilitate the pedaling in safety.
- **Folding frame** to save space during transport.
- **Adjustable handlebar** in height, backward-forward and reversible.
- **Wide and ergonomic handles**, to increase comfort.
- **Bell**.
- **Front and back led lamp**.
- **Front brake with locking device** for ascent and descent, that can be operated by the lever either on the right or on the left side of the handlebar. The distance between the brake lever and the handlebar is adjustable by screw.
- **Adjustable ergonomic saddle** in height, tilt and backward-forward
- **Rear storage basket**.
- **16" pneus wheels**. A mechanism on the rear wheels allows easy adjustment of the tension of the chain.
- **Quick release front wheel**.



Attention!
Read carefully the user and maintenance manual

Please check off the interested products: ☒ _____


MEASURES

FRAME COLOUR:


- ☐ Blue
- ☐ Red
- ☐ Green

Storage basket
Internal measures


View from above



L	49,7 cm	In 19,5
M	27,4 cm	In 10,7
N	9,6 cm	In 3,6
Max. Load	25 kg	Lb 55



C1= C2-2cm



C2= leg length

	Max. Load	Aid Weight	A	B	C1*	D	E	F	G	I	User Height (H)
Medium	kg. 60 lb 132,2	kg. 23 lb. 50,7	cm 55 in 21,6	cm 75 in 29,5	cm 59-72 in 23,2-28,3	cm 16 in 6,3	cm 136 in 53,5	cm 45 in 17,7	cm 81 in 31,8	cm 90 in 35,4	cm 120-145 in 47,2-57

*With standard saddle. You can further adjust the height of the saddle (± 3 cm) acting on the clamp.

Choose the configuration



Fixed Pinion



Free Wheel



Differential and Fixed Pinion



Differential and Free Wheel



NEW Differential and "Switch" system. Allows you to switch from freewheel to fixed pinion and vice versa.



Three-speed transmission with differential. Allows braking by counter-pedaling, shifting when the tricycle is stationary, and reversing.

OPTIONAL COMPONENTS, ONLY CHOOSABLE WHEN ORDERING THE TRICYCLE

☐ **864** Disc brake. Only for models with differential and without gearbox. Not available with "Switch" system.



Standard handlebar

☐ S

☐ M

☐ Left

☐ Right

Please choose the position of the brake. In the absence of indications, the brake will be mounted on the right.



☐ **847** Cranks adjustable in length decreases the distance between saddle and pedal of 3,5 cm.



OPTIONAL COMPONENTS, ALSO CHOOSABLE SEPARATELY

☐ **880** Ergonomic handles adjustable in inclination independently (1 pair). Same size as the Handlebar.

Choose the position of the brake on Ergonomic Handles



845 Forearm support.

☐ Left

☐ Right

☐ mini

☐ S-M



875 Wrist retainer with support and multi-adjustable glove independently.

☐ Left

☐ Right

☐ mini

☐ S-M



842P Pelvic support with belt, adjustable in height.

Also select the component 883

☐ mini-S

☐ M



842T Trunk support, adjustable in height, inclination and backward-forward with belt and joint. Also select the component 883.

☐ mini-S

☐ M



☐ **883** Rod adjustable in height for Thoracic/Pelvic support (single rod). Please select even the type of support.



☐ **877** Flat backrest.



☐ **843** Abductive saddle with holder for supports.



☐ **876** Monocycle saddle with holder for supports.



☐ **103** Monocycle saddle padding.



☐ **112** Comfortable larger saddle, with wider support surface.




☐ **840** Pedal cages with straps (1 pair).



841 Pedal cage with length and width adjustable foot imprints and fastening straps, with support kit.

☐ Left

☐ Right



846 Ankle support adjustable in height, with support kit. Only with component 841.

☐ Left

☐ Right

☐ S-M

☐ L-XL



☐ **923** Additional assistant handle.



☐ **963** Steering assistant handle adjustable in height. Cannot be installed with 881 or 882 components.



☐ **881** Steering limiter.



☐ **882** Steering limiter with springs to return the steering to the straight position.



☐ **879** Front basket.




☐ **878** 878 MTB tires (3 pcs.) in alternative to standard tyres.




COMPONENTS
MEASURES

842P




	A
mini/s	8,5-14 cm/3,3-5,5 in
M	8,5-21 cm/3,3-8,3 in
L/XL	8,5-23 cm/3,3-9 in

842T




	A
mini/s	19-30,5 cm/7,4-12 in
M	19-40 cm/7,4-15,7 in
L/XL	19-46 cm/7,4-18,1 in

842P - 842T




	B	C
mini/s	10,5 cm/4,1 in	23 cm/9 in
M	12,5 cm/4,9 in	31 cm/12,2 in
L/XL	17,5 cm/6,8 in	35 cm/13,7 in

843




	A	B
mini/s	31 cm/12,2 in	12,5 cm/4,9 in
M/L/XL	40 cm/15,7 in	14 cm/5,5 in

876




A	31 cm 12,2 in
B	13,5 cm 5,3 in
C	9 cm 3,5 in

Standard saddle




	A	B
mini/s	25 cm 9,8 in	17 cm 6,7 in
M/L/XL	25,5 cm 10 in	20 cm 7,8 in

112




	A	B
mini/s	25,5 cm 10 in	20 cm 7,8 in
M/L/XL	25,5 cm 10 in	24,5 cm 9,6 in

841



841 foot imprint size			
	A	B	C
mini/s	from 5 to 7 cm from 1,9 to 2,7 in	from 12,5 to 16,5 cm from 4,9 to 6,5 in	from 6 to 7 cm from 2,3 to 2,7 in
M/L/XL	from 8,2 to 9,4 cm from 3,2 to 3,7 in	from 20 to 22,5 cm from 7,8 to 8,8 in	from 10,4 to 12 cm from 4 to 4,7 in

Standard handlebar



	A
mini	45 cm / 17,7 in
S	50 cm / 19,6 in
M	55 cm / 21,6 in
L	60 cm / 23,6 in
XL	64 cm / 25,2 in

Notes: _____
