

• MADE IN ITALY SINCE 1980

DISTRIBUTOR/AGENT:



ORDER FORM

	Jahra	PATEN	TED
E,			
8			7

The alternative to being bedridden

• FRAME made of chromed steel, painted with non-toxic epoxy powder paint. Narrow base to facilitate entering elevators.

• The seat and backrest are covered with visco-elastic fire-proof material. It is resistant, breathable and anti-slip. It is made of a special and exclusive ORMESA formula:

DATE OF ORDER:

DATE OF DELIVERY

NAME OF THE ADDRESSEE/USER:

- 1) It adapts to the user's body shapes and it prevents its sliding, with the result of an EXCELLENT COMFORT and KEEPING POSTUR even when changing the backrest recline and tilt (it adapts to the user's body shapes maintaining its support function).
- 2)Easily washable to keep the HYGIENE of the user; It lets AIR PASS keeping the OPTIMAL MICROCLIMATE that HELPS PREVENTING BED SORES.
- 3) Durable and fireproof, GUARANTEE OF DURABILITY and SAFETY.
- 4) Ergonomic, breathable, non-toxic, fireproof UPHOLSTERY; It does not interfere with the benefits of the visco-elastic cover. The upholstery is fixed with buttons, easy to remove for machine washing.
- Ergonomic BACKREST, it holds the shapes of the user. The special structure of the backrest gives a proper alignment to the trunk and it doesn't generate any pressure on the spine. Adjustable in till by levers with safety pin. The pin allows blocking the levers to maintain the proper adjustment for the user, height adjustable, folding for transportation.
- Low SEAT and slightly inclined. Adjustable in depth on four positions.
- Wide and wrap HEADREST, padded, multi adjustable (in height, tilt, depth, lateral traslation); thus assuring the proper alignment between head and trunk, without interfering with the user's view. Anti-bacterial and Hygienic.
- ARMRESTS, padded, easily and stably adjustable in height thanks to the lever.
- PUSH HANDLE adjustable in tilt/ height, it helps the care.
- CONTINUOUS AND WITHOUT EFFORT ADJUSTMENTS: tilting, backrest recline and legrest tilt are operated by independent gas springs.
- SIDES with scissor opening. Thanks to the special joint, the armrests are positioned behind the backrest, eliminating completely all obstacles to the transfer.
- LEG RESTS: ergonomic, removable, turnable and adjustable in tilt without effort, activated with aas springs,
- CALFRESTS adjustable in depth and free tilt to accommodate the movements of the leq.
- FOOT RESTS, adjustable in flexion-extension and height.
- 5" SOLID SWIVELING WHEELS, the rear ones with brakes.

(£ Marked

$\dot{\mathbb{N}}$

Attention! Read carefully the user and maintenance

Please check off the interested products:

se chec	JK OII tii	e mien	esteu p	roducts.	
SIZES:	3 6	4 0	45	□ 50	

dark grey ☐ light grey UPHOLSTERY COLOUR:


FRAME COLOUR:

M-

■ white

■ black







*footrest adjusted to the maximum length

eat bottom width	B seat bottom depth	C backrest width	D overall width	H seat bottom inclination-tilt	backrest inclination	Total weight	Max. Capacity	User height	
36 cm	40-43-46-49 cm	47 cm	60 cm	from 10° to 35° from	from 100 to 250	from 100 to 200	37 kg	120 kg	from 140 to 190 cm
14,1 in	15,7-16,9-18,1-19,2 in	18,5 in	23,6 in		10 35	81,5 lb	264,5 lb	from 55,1 to 74,8 in	
40 cm	40-43-46-49 cm	47 cm	60 cm	from 10° to 35°	from 100 to 250	from 100 to 200	37 kg	120 kg	from 140 to 190 cm
15,7 in	15,7-16,9-18,1-19,2 in	18,5 in	23,6 in		011110-1035- 11011110-1038-	81,5 lb	264,5 lb	from 55,1 to 74,8 in	
45 cm	40-43-46-49 cm	52 cm	65 cm	from 10° to 35°		100	39 kg	130 kg	from 140 to 190 cm
17,7 in	15,7-16,9-18,1-19,2 in	20,4 in	25,5 in		from 10° to 38°	85,9 lb	286,6 lb	from 55,1 to 74,8 in	
50 cm	40-43-46-49 cm	57 cm	70 cm	from 10° to 35°	f==== 100 t= 250	frame 100 to 200	40 kg	140 kg	from 140 to 190 cm
19,6 in	15,7-16,9-18,1-19,2 in	22,4 in	27,5 in		10111 10° 10 35° 110m 10° to 38°	88,1 lb	308,6 lb	from 55,1 to 74,8 in	
	width 36 cm 14,1 in 40 cm 15,7 in 45 cm 17,7 in 50 cm	width depth 36 cm 40-43-46-49 cm 14,1 in 15,7-16,9-18,1-19,2 in 40 cm 40-43-46-49 cm 15,7 in 15,7-16,9-18,1-19,2 in 45 cm 40-43-46-49 cm 17,7 in 15,7-16,9-18,1-19,2 in 50 cm 40-43-46-49 cm	width depth width 36 cm 40-43-46-49 cm 47 cm 14,1 in 15,7-16,9-18,1-19,2 in 18,5 in 40 cm 40-43-46-49 cm 47 cm 15,7 in 15,7-16,9-18,1-19,2 in 18,5 in 45 cm 40-43-46-49 cm 52 cm 17,7 in 15,7-16,9-18,1-19,2 in 20,4 in 50 cm 40-43-46-49 cm 57 cm	width depth width width 36 cm 40-43-46-49 cm 47 cm 60 cm 14,1 in 15,7-16,9-18,1-19,2 in 18,5 in 23,6 in 40 cm 40-43-46-49 cm 47 cm 60 cm 15,7 in 15,7-16,9-18,1-19,2 in 18,5 in 23,6 in 45 cm 40-43-46-49 cm 52 cm 65 cm 17,7 in 15,7-16,9-18,1-19,2 in 20,4 in 25,5 in 50 cm 40-43-46-49 cm 57 cm 70 cm	width depth width width inclination-tilt 36 cm 40-43-46-49 cm 47 cm 60 cm from 10° to 35° 14,1 in 15,7-16,9-18,1-19,2 in 18,5 in 23,6 in from 10° to 35° 40 cm 40-43-46-49 cm 47 cm 60 cm from 10° to 35° 15,7 in 15,7-16,9-18,1-19,2 in 18,5 in 23,6 in from 10° to 35° 45 cm 40-43-46-49 cm 52 cm 65 cm from 10° to 35° 17,7 in 15,7-16,9-18,1-19,2 in 20,4 in 25,5 in from 10° to 35° 50 cm 40-43-46-49 cm 57 cm 70 cm from 10° to 35°	width depth width width inclination-tilt inclination 36 cm 40-43-46-49 cm 47 cm 60 cm from 10° to 35° from 10° to 38° 40 cm 40-43-46-49 cm 47 cm 60 cm from 10° to 35° from 10° to 38° 15,7 in 15,7-16,9-18,1-19,2 in 18,5 in 23,6 in from 10° to 35° from 10° to 38° 45 cm 40-43-46-49 cm 52 cm 65 cm from 10° to 35° from 10° to 38° 50 cm 40-43-46-49 cm 57 cm 70 cm from 10° to 35° from 10° to 38°	Motion Sect Sottom Sect Sottom width Sect Sottom width sect Sottom width sect Sottom weight 36 cm 40-43-46-49 cm 47 cm 60 cm from 10° to 35° 37 kg 14,1 in 15,7-16,9-18,1-19,2 in 18,5 in 23,6 in from 10° to 35° 37 kg 40 cm 40-43-46-49 cm 47 cm 60 cm from 10° to 35° 37 kg 15,7-16,9-18,1-19,2 in 18,5 in 23,6 in from 10° to 35° 81,5 lb 45 cm 40-43-46-49 cm 52 cm 65 cm from 10° to 35° from 10° to 38° 39 kg 17,7 in 15,7-16,9-18,1-19,2 in 20,4 in 25,5 in from 10° to 35° from 10° to 38° 85,9 lb 50 cm 40-43-46-49 cm 57 cm 70 cm from 10° to 35° from 10° to 38° 40 kg	Motion Sect bottom Sect bottom weight Capacity 36 cm 40-43-46-49 cm 47 cm 60 cm from 10° to 35° 37 kg 120 kg 14,1 in 15,7-16,9-18,1-19,2 in 18,5 in 23,6 in from 10° to 35° from 10° to 38° 37 kg 120 kg 40 cm 40-43-46-49 cm 47 cm 60 cm from 10° to 35° 37 kg 120 kg 15,7-16,9-18,1-19,2 in 18,5 in 23,6 in from 10° to 35° 81,5 lb 264,5 lb 45 cm 40-43-46-49 cm 52 cm 65 cm from 10° to 35° 39 kg 130 kg 17,7 in 15,7-16,9-18,1-19,2 in 20,4 in 25,5 in from 10° to 35° from 10° to 38° 85,9 lb 286,6 lb 50 cm 40-43-46-49 cm 57 cm 70 cm from 10° to 38° from 10° to 38° 40 kg 140 kg	

Hyphen separated numbers indicate a minimum and maximum range of adjustment







S U

R E S





• MADE IN ITALY SINCE 1980 •





