

DISTRIBUTOR/AGENT:	DATE OF ORDER:
	DATE OF DELIVERY:
	NAME OF THE ADDRESSEE/USER:



Product marked

FEATURES

- **Ergonomic and modular tricycle** that helps the user to keep a proper posture and makes the ride easier thanks to its design and components.
- **Lowered frame** for easy ascent and descent.
- **Front positioned bottom bracket** for easier pedaling.
- **Pinion** to facilitate the pedaling in safety.
- **Folding frame** to save space during transport.
- **Adjustable handlebar** in height, backward-forward and reversible.
- **Wide and ergonomic handles**, to increase comfort.
- **Bell**.
- **Front and back led lamp**.
- **Front brake with locking device** for ascent and descent, that can be operated by the lever either on the right or on the left side of the handlebar. The distance between the brake lever and the handlebar is adjustable by screw.
- **Adjustable ergonomic saddle** in height, tilt and backward-forward
- **Rear storage basket**.
- **20" pneus wheels**. A mechanism on the rear wheels allows easy adjustment of the tension of the chain.
- **Quick release front wheel**.



Attention!
Read carefully the user and maintenance manual


Please check off the interested products: ☒ _____

FRAME COLOUR:

- ☐ Blue
- ☐ Red
- ☐ Green

Storage basket Internal measures


View from above




L	49,7 cm	in 19,5
M	27,4 cm	in 10,7
N	9,6 cm	in 3,7
Max. load	35 kg	lb 77



MEASURES



C1= C2-2cm



C2= leg length

	Max. Load	Aid Weight	A	B	C1*	D	E	F	G	I	User Height (H)
Large	kg. 90 lb. 198,4	kg. 25,5 lb. 56,2	cm 60 in 23,6	cm 75 in 29,5	cm 69-83 in 27,1-32,6	cm 16 in 6,3	cm 162 in 63,7	cm 56,5 in 22,2	cm 95 in 37,4	cm 100 in 39,3	cm 140-165 in 55,1-64,9

*With standard saddle. You can further adjust the height of the saddle (± 3 cm) acting on the clamp.

Choose the configuration

☐ Fixed Pinion	☐ Free Wheel	☐ Differential and Fixed Pinion	☐ Differential and Free Wheel	☐ Differential and "Switch" system. It allows you to switch from freewheel to fixed pinion and vice versa. NEW	☐ Three-speed transmission with differential. Allows braking by counter-pedaling, shifting when the tricycle is stationary, and reversing.
---------------------------------------	-------------------------------------	--	--	--	---

OPTIONAL COMPONENTS, ONLY CHOOSABLE WHEN ORDERING THE TRICYCLE

☐ 864 Disc brake. Only for models with differential and without gearbox. Not available with "Switch" system.	☐ 847 Cranks adjustable in length decreases the distance between saddle and pedal of 3,5 and 5 cm.	Handlebar ☐ Left ☐ Right ☐ M ☐ L	Please choose the position of the brake, in absence of indications, the brake will be mounted on the right.
--	--	---	---

OPTIONAL COMPONENTS, ALSO CHOOSABLE SEPARATELY

☐ 880 Ergonomic handles adjustable in inclination independently (1 pair). Same size as the Handlebar. Choose the position of the brake on Ergonomic Handles	☐ 845 Forearm support. Size L-XL ☐ Left ☐ Right	☐ 875 Wrist retainer with support and multi-adjustable glove independently. Size L-XL. ☐ Left ☐ Right	☐ 842P Pelvic support with belt, adjustable in height. Also select the component 883. ☐ M ☐ L-XL
☐ 842T Trunk support, adjustable in height, inclination and backward-forward with belt and joint. Also select the component 883. ☐ M ☐ L-XL	☐ 883 Rod adjustable in height for Thoracic/Pelvic support (single rod). Please select even the type of support.	☐ 877 Flat backrest.	☐ 116 Parking brake lever. NEW
☐ 843 Abductive saddle with holder for supports.	☐ 876 Monocycle saddle with holder for supports.	☐ 103 Monocycle saddle padding.	☐ 112 Comfortable larger saddle, with wider support surface. NEW
☐ 113 Standard and larger saddle cover. NEW	☐ 840 Pedal cages with straps (1 pair).	☐ 841 Pedal cage with length and width adjustable foot imprints and fastening straps, with support kit. ☐ Left ☐ Right	☐ 846 Ankle support adjustable in height, with support kit. Only with component 841. ☐ Left ☐ Right ☐ S-M ☐ L-XL

☐ **881** steering limiter.



☐ **882** Steering limiter with springs to return the steering to the straight position.



☐ **879** Front basket.




☐ **878** 878 MTB tires (3 pcs.) in alternative to standard tyres.




M I S U R E
C O M P O N E N T I

842P




	A
mini/s	8,5-14 cm
M	8,5-21 cm
L/XL	8,5-23 cm

842T




	A
mini/s	19-30,5 cm
M	19-40 cm
L/XL	19-46 cm

842P - 842T




	B	C
mini/s	10,5 cm	23 cm
M	12,5 cm	31 cm
L/XL	17,5 cm	35 cm

843




	A	B
mini/s	31 cm	12,5 cm
M/L/XL	40 cm	14 cm

876




A	31 cm
B	13,5 cm
C	9 cm

Sella standard




	A	B
mini/s	25 cm	17 cm
M/L/XL	25,5 cm	20 cm

112




	A	B
mini/s	25,5 cm	20 cm
M/L/XL	25,5 cm	24,5 cm

841



	misure impronta 841		
	A	B	C
mini/s	da 5 a 7 cm	da 12,5 a 16,5 cm	da 6 a 7 cm
M/L/XL	da 8,2 a 9,4 cm	da 20 a 24 cm	da 10,4 a 12 cm

Manubrio standard



	A
mini	45 cm
S	50 cm
M	55 cm
L	60 cm
XL	64 cm

Notes: _____
